

## ILS or LOC RWY 31

LOC I-BNN <b>108.3</b>	APCH CRS <b>308°</b>	Rwy Idg <b>8194</b> TDZE <b>4270</b> Arprt Elev <b>4295</b>	[USAF]	CANNON AFB (KCVS)
---------------------------	-------------------------	---	--------	-------------------

ATC RADAR or DME required. Missed approach requires use of RNAV or ATC RADAR monitoring.

**\* When ALS inop, increase vis to ¾ mile.**

ATIS <b>119.1 269.9</b>	CANNON APP CON <b>118.425 352.1</b>	CANNON TOWER <b>120.4 270.25</b>	GND CON <b>121.9 275.8</b>	CLNC DEL <b>120.2 293.225</b>
----------------------------	--	-------------------------------------	-------------------------------	----------------------------------

**\*\* When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1 ½ miles.**

EMERG SAFE ALT 100 NM 9000

6000 ↑	LERAY CVS <b>5.5</b>	7000 ↖	VGSI TCH (41') and the procedure TCH (51') is greater than 3'.	
-----------	-------------------------	-----------	--	--

CATEGORY	A	B	C	D	E
S-ILS 31*	4470-½ (200-½)				
S-LOC 31**	4660-½	390 (400-½)	4660-⅝	390 (400-⅝)	
CIRCLING	4840-1				
	545 (600-1)	4860-1½	5000-2¼	5020-2½	

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:33