RNAV (RNP) Z RWY 5L

RALEIGH-DURHAM INTL (RDU)

APP CRS	Rwy Ldg	10000
054°	TDZE	384
	Apt Elev	435

RNP AR APCH-GPS.

For uncompensated Baro-VNAV systems, procedure NA below -12°C or above 54°C. Simultaneous approach authorized, except for arrivals at HEAVE. For inop ALS, increase RNP 0.10 all Cats visibility to RVR 4500.

MALSR

MISSED APPROACH: Climb to 1000 then climbing left turn to 2200 direct DUHAM and hold.

D-ATIS	RALEIGH APP CON	RALEIGH TOWER	GND CON	CLNC DEL	CPDLC
123.8	127.675 307.9	127.45 257.8	121.9 348.6	120.1	

MISSED APCH FIX

4 NM 173° 353° DUHAM

(IF) HEAVE 6000 210K until WEPAS (RF REQD)

4700 234° (1.6) ZOSAP

5100 234° (2.7) JEMMY

RW05L

(FAF) WEPAS 2200 (7.9) 054° (5.6)

3000 054° (2.7) (IF) SCHOO

2200 054° (3)

BOULE

4000 054° (3.1)

5000 068° (6.4) (IAF) CHWDR 210K

(IAF) OTTOS 6000 210K

MSA RW05L 25 NM 3400

ELEV 435 D TDZE 384

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).

1000 2200 DUHAM

See planview for multiple IF locations.

WEPAS 2200 054° RW05L

GP 3.00° TCH 57

2200

5.6 NM

CATEGORY	A	B	C	D
RNP 0.10 DA	684/24 300 (300-½)			
RNP 0.30 DA	780/35 396 (400-⅝)			

AUTHORIZATION REQUIRED

TWR

10000 X 150

0.6% UP

7500 X 150

0.4% UP

3570 X 100

REIL Rwy 32

MIRL Rwy 14-32

HIRL Rwys 5R-23L and 5L-23R

TDZ/CL Rwys 5L, 23L, and 23R

SE-2, 07 AUG 2025 to 04 SEP 2025

SE-2, 07 AUG 2025 to 04 SEP 2025