

ILS or LOC RWY 13

LOC I-ATB 111.7	APCH CRS 127°	Rwy ldg 10,695' TDZE 1048' Arprt Elev 1048'	[USAF]	OFFUTT AFB (KOFF)
---------------------------	-------------------------	--	--------	-------------------

RADAR or DME required
 * When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1 1/2 miles.
 ** Circling not authorized N of Rwy 13-31.

ATIS 126.025 273.5	OMAHA APP CON 124.5 263.0 (E) 135.875 354.05 (W)	TOWER 123.7 279.625	GND CON 121.7 289.4
------------------------------	--	-------------------------------	-------------------------------

EMERG SAFE ALT 100 NM 4700

OFFUTT Chan 54 OFF	LOCALIZER 111.7 I-ATB	TYTAN OFF 12	ELEV 1048	TDZE 1048
-----------------------	--------------------------	--------------	-----------	-----------

CATEGORY	A	B	C	D	E
S-ILS 13	1298/50 250 (300-1)				
S-LOC 13*	1560/50	512 (600-1)	1560/55	512	(600-1)
CIRCLING	1560-1	512 (600-1)	1660-1 612 (700-134)	1940-3	892 (900-3)

FAF to MAP 4.9 NM					
Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38