


LOC/DME I-CJL 110.75 Chan 44 (Y)	APP CRS 164°	Rwy Idg TDZE Apt Elev	8500 415 432	ILS RWY 16R (CAT II & III) SEATTLE-TACOMA INTL (SEA)
DME or RADAR required. From GRIFY: RNAV 1-GPS required.				

Simultaneous approach authorized with Rwy 16L and 16C. Simultaneous operations require use of vertical guidance, maintain last assigned altitude until established on glideslope. Cat II: RVR 1000 authorized with specific OPSPEC, MSPEC or LOA approval and use of Autoland or HUD to touchdown.

ALSF-2

MISSED APPROACH: Climb to 900 then climb on heading 195° and on SEA VORTAC R-210 to cross TECEE/SEA 3 DME/RADAR at or below 2000 then climb to 5000 on SEA VORTAC R-210 to ZERLI/SEA 15 DME/RADAR and hold, continue climb-in-hold to 5000.

D-ATIS 118.0	SEATTLE APP CON 133.65 273.45	SEATTLE TOWER 119.9 239.3 (Rwys 16L, 16C, 34C, 34R) 120.95 239.3 (Rwys 16R, 34L)	GND CON 121.7	CLNC DEL 128.0	CPDLC
------------------------	---	--	-------------------------	--------------------------	-------



900 ↑ hdg 195° SEA R-210	TECEE SEA 3 2000	5000 ↑ SEA R-210	ZERLI SEA 15	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 69).				ZIKRO I-CJL 22.1 RADAR
FINKA I-CJL 6.1 RADAR		BUGNE I-CJL 10.1 RADAR		CELAK I-CJL 12.7 RADAR	AGANE I-CJL 15.8 RADAR	CIBUX I-CJL 18.9 RADAR	164° 7000	
1900		3200		4000	5000	6000	GS 3.00° TCH 55	
1148		4.5 NM	4.1 NM	2.5 NM	3.1 NM	3.1 NM	3.1 NM	
CATEGORY	A		B		C		D	
S-ILS 16R	CAT II RA 139/12 100 DA 515							
S-ILS 16R	CAT III RVR 03							
CATEGORY II & III ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED								

