

WAAS CH <b>40001</b> <b>W06A</b>	APP CRS <b>056°</b>	Rwy Idg <b>6997</b> TDZE <b>380</b> Apt Elev <b>398</b>
--	------------------------	---

RNAV (GPS) RWY 6

COLUMBUS (CSG)

RNP APCH - GPS.


⚠

Circling to Rwy 13, 31 and 24 NA at night. Rwy 6 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 54°C. For inop ALS, increase LPV all Cats visibility to RVR 4500. For inop ALS, increase LNAV Cats A and B visibility to RVR 5500 and Cats C and D visibility to 1½ SM.


MALSR

MISSED APPROACH: Climb to 900, then climbing left turn to 2500 direct GEMMY and hold.

ATIS <b>127.75</b>	ATLANTA APP CON ★ <b>125.5 323.1</b>	COLUMBUS TOWER ★ <b>120.1 (CTAF) 0 257.8</b>	GND CON <b>121.9 348.6</b>	UNICOM <b>122.95</b>
-----------------------	---	---	-------------------------------	-------------------------



ELEV 398	<b>D</b>	TDZE 380
----------	----------	----------



CATEGORY	A	B	C	D
LPV DA		659/40	279 (300-¾)	
LNAV/VNAV DA		832/45	452 (500-¾)	
LNAV MDA	960/40	580 (600-¾)	960-1¼	580 (600-1¼)
<b>C</b> CIRCLING	960-1	562 (600-1)	1140-2¼ 742 (800-2¼)	1300-3 902 (1000-3)

