

APP CRS
186°

Rwy Ldg
10000

TDZE
889

Apt Elev
896

RNAV (RNP) Z RWY 18L

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

RNP AR APCH - GPS. Authorization required. From NABRS or OCONO: RF.

▼

For uncompensated Baro-VNAV systems, procedure NA below -14°C or above 54°C.
For inop ALS, increase RNP 0.25 all Cats visibility to 5500 and increase RNP 0.30 all
Cats visibility to 1½ SM. Simultaneous approach authorized.

MALSR

AS

MISSED APPROACH: Climb
to 3000 direct LAPER and on
track 136° to FLM VOR/DME
and hold.

D-ATIS	CINCINNATI APP CON	CINCINNATI TOWER	GND CON	CLNC DEL	CPDLC
ARR 134.375	DEP 135.3	119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	118.975 360.85 (RWY 18L/36R) 118.3 (RWYS 18C/36C, 09/27) 133.325 (RWY 18R/36L)	121.7	127.175

ELEV 896

D

TDZE 889

3000	LAPER	tr 136°	FLM	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00°/TCH 71).
See planview for multiple IF locations.				
GP 3.00° TCH 55				
CATEGORY	A	B	C	D
RNP 0.25 DA		1240/30	351 (400-5%)	
RNP 0.30 DA		1388/50	499 (500-1)	

AUTHORIZATION REQUIRED

COVINGTON, KENTUCKY

Amdt 1 12JUN25

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

39°03'N-84°40'W

RNAV (RNP) Z RWY 18L