

## RNAV (GPS) RWY 6

OWENSBORO/DAVIESS COUNTY RGNL (OWB)

WAAS CH <b>40430</b> <b>W06A</b>	APP CRS <b>056°</b>	Rwy Idg <b>5000</b> TDZE <b>405</b> Apt Elev <b>407</b>
--	------------------------	---

For uncompensated baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Rwy 6 helicopter visibility reduction below ¼ SM NA. When local altimeter setting not received, use Evansville altimeter setting: increase LPV DA to 719 feet and all Cats visibility ½ mile; increase LNAV/VNAV DA to 734 feet and all Cats visibility ¼ mile; increase all MDA 60 feet and LNAV Cats C/D and Circling Cats C/D visibility ¼ mile. Baro-VNAV and VDP NA when using Evansville altimeter setting.

**MISSED APPROACH:**  
Climb to 3000 direct  
CINU and hold.

AWOS-3PT <b>119.025</b>	EVANSVILLE APP CON ★ <b>124.025 290.9</b>	OWENSBORO TOWER ★ <b>120.7 (CTAF) 0 251.15</b>	GND CON <b>121.7</b>	UNICOM <b>122.95</b>
----------------------------	--	---	-------------------------	-------------------------

