


VOR RWY 18
WITTMAN RGNL (OSH)

MISSED APPROACH: Climbing left turn to 3000 on OSH VORTAC R-111 to LEWKO INT/OSH 15.1 DME and hold.

UNICOM
122.95

EC-3, 07 AUG 2025 to 04 SEP 2025

The diagram illustrates the construction of a women's vest pattern. Key components and measurements include:

- Neckline:** A curved line labeled "3000" and "OSH R-111".
- Shoulder:** A horizontal line labeled "LEWKO" with a triangle symbol.
- Back:** A vertical line labeled "OSH VORTAC".
- Armhole:** A curved line labeled "006°".
- Waist:** A horizontal line labeled "2600".
- Side Seam:** A line labeled "186°" and "WOMEN OSH 1.8".
- Bottom:** A horizontal line labeled "1480".
- Construction Notes:**
 - *1520 when using Fond Du Lac altimeter setting.
 - ≤ 2.92°
 - TCH 47
 - 0.2, 1.1, 0.7 NM (likely millimeters)

CATEGORY	A	B	C	D
S-18	1480-1	686 (700-1)	1480-2	686 (700-2)
C CIRCLING	1480-1	672 (700-1)	1480-2 672 (700-2)	1480-2 1/4 672 (700-2 1/4)

WOMEN FIX MINIMUMS

	1260-1	466 (500-1)	1260-1 3/8	466 (500-1 3/8)
S-18	1280-1	472 (500-1)	1300-1	492 (500-1)
C CIRCLING	1280-1 472 (500-1)	1300-1 492 (500-1)	1360-1 1/2 552 (600-1 1/2)	1440-2 632 (700-2)

WITTMAN RGNL (OSH)
VOR RWY 18