


WAAS CH 48902 W10A	APP CRS 096°	Rwy Idg TDZE 7 Apt Elev 65
--	------------------------	--

RNAV (GPS) Z RWY 10L

FORT LAUDERDALE/HOLLYWOOD INTL (FLL)

RNP APCH-GPS.				<div>MALSR</div> <div></div>	<div>MISSED APPROACH: Climb to 800 then climbing left turn to 4000 direct MARTS and hold. Continue climb-in-hold to 4000.</div>	
<div><div>▼</div><div>▲</div></div> <div>For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 7°C or above 54°C. Inop table does not apply to LPV all Cats. LNAV procedure NA during simultaneous operations. For inop ALS, increase LNAV/VNAV visibility all Cats to 1½ SM, LNAV visibility Cat A and B to RVR 5500 and Cats C/D to RVR 6000. Use of FD or AP required during simultaneous operations. Simultaneous approach authorized.</div>						
<div>D-ATIS</div> <div>135.0</div>	<div>MIAMI APP CON</div> <div>133.775 285.6</div>	<div>FORT LAUDERDALE TOWER</div> <div>119.3 257.8</div>	<div>GND CON</div> <div>121.4</div>	<div>CLNC DEL</div> <div>128.4</div>	<div>CPDLC</div>	

