

WAAS CH <b>78311</b> <b>W17A</b>	APP CRS <b>172°</b>	Rwy Idg <b>5900</b> TDZE <b>248</b> Apt Elev <b>250</b>
--	------------------------	--

RNAV (GPS) RWY 17

CORVALLIS MUNI (CVO)

RNP APCH - GPS.

Circling Rwy 28 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, procedure NA. For inop ALS, increase LNAV Cat C/D visibility to 1¼ SM.

MALSR

MISSED APPROACH: Climb to 1100 then climbing left turn to 3700 direct INNOP and hold, continue climb-in-hold to 3700.

AWOS-3PT <b>135.775</b>	CASCADE APP CON ★ <b>127.5 348.7</b>	UNICOM <b>123.075</b> (CTAF) <b>0</b>
----------------------------	---	--

Procedure NA for arrivals at CRAAF on V287 northeast bound.

• 2686

• 2096

• 4097

Procedure NA for arrivals at MAGOT on V23 northbound.

MSA RW17 25 NM **5300** **Δ1632**

ELEV **250** **D** TDZE **248**

172°

3100 X 75

5900 X 150

35

REIL Rwy 35 **0**

HIRL Rwy 17-35 **0**

MIRL Rwy 10-28 **0**

1100	3700	INNOP	INNOP	4 NM Holding Pattern
ACVOL	EGBEW	INNOP		
CAYJU 2.5 NM to RW17	2400	2900	6000	3700
1.8 NM to RW17	1080	2400		GP 3.00° TCH 45
1.8 NM	0.7	4.1 NM	2 NM	3.9 NM
CATEGORY	A	B	C	D
LPV DA	448-½ 200 (200-½)			
LNAV/VNAV DA	571-½ 323 (400-½)			
LNAV MDA	880-½ 632 (700-½)		880-1⅓ 632 (700-1⅓)	
CIRCLING	880-1 630 (700-1)		920-1¾ 670 (700-1¾)	1080-2¾ 830 (900-2¾)

CORVALLIS, OREGON  
Amdt 1B 07OCT21

44°30'N-123°17'W

CORVALLIS MUNI (CVO)

RNAV (GPS) RWY 17

NW-1, 07 AUG 2025 to 04 SEP 2025

NW-1, 07 AUG 2025 to 04 SEP 2025