

WAAS

CH **53510**

W04A

APP CRS

038°

Rwy Idg

7098

TDZE

763

Apt Elev

768

RNAV (GPS) RWY 4

QUINCY RGNL-BALDWIN FLD (UIN)

RNP APCH - GPS.

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. Baro-VNAV and VDP NA when using PPG altimeter setting. When local altimeter setting not received, use Pittsfield altimeter setting and increase LPV DA to 1033 feet; increase LNAV/VNAV DA to 1104 feet and all visibilities ½ SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D ¾ SM. For inop ALS when local altimeter setting not received, increase LPV all Cats visibility to ¾ SM; increase LNAV/VNAV all Cats visibility to 1 SM; increase LNAV Cat C and D visibility to 1 ¾ SM. For inop ALS increase LNAV/VNAV all Cats visibility to ¾ SM.

▲

MISSED APPROACH: Climb to 2400 direct FANUT and hold.

MALSR

ASOS 121.425	KANSAS CITY CENTER 126.225 317.775	UNICOM 123.0 (CTAF) 0
------------------------	--	---------------------------------

MISSED APCH FIX

HOWARD WEST MOA

HOWARD EAST MOA

PRUITT A MOA

4 NM Holding Pattern

GP 3.00°

TCH 41

WUSIS

2100

1.1 NM to RW04

RW04

6.2 NM

3 NM

1.1 NM

2400

FANUT

ELEV 768

TDZE 763

CATEGORY	A	B	C	D
LPV DA	963-1½ 200 (200-½)			
LNAV/VNAV DA	1034-1½ 271 (300-½)			
LNAV MDA	1160-½ 397 (400-½)	1160-5⁄8 397 (400-5⁄8)		
CIRCLING	1180-1 412 (500-1)	1220-1 452 (500-1)	1240-1½ 472 (500-1½)	1320-2 552 (600-2)

HRL Rwy 4-22 0

MRL Rwy 13-31 0

REIL Rwy 22 0

QUINCY, ILLINOIS

Amdt 1 26DEC24

39°57'N-91°12'W

QUINCY RGNL-BALDWIN FLD (UIN)

RNAV (GPS) RWY 4