

WAAS CH <b>40420</b> <b>W18A</b>	APP CRS <b>178°</b>	Rwy Idg <b>5998</b> TDZE <b>206</b> Apt Elev <b>206</b>
--	------------------------	---

RNAV (GPS) RWY 18  
PINEBLUFF RGNL/GRIDER FLD (PBF)

RNP APCH - GPS.

**T** Baro-VNAV and VDP NA when using Stuttgart altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -10°C or above 54°C. When local altimeter setting not received, use Stuttgart altimeter setting and increase LPV DA to 534 feet; increase LNAV/VNAV DA to 723 feet and all visibilities ½ SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat C/D ¼ SM. For inop ALS, increase LNAV Cats A/B visibility to 1 SM and Cats C/D visibility to 1½ SM. For inop ALS when using Stuttgart altimeter setting, increase LPV all Cats visibility to 1 SM; increase LNAV/VNAV all Cats visibility to 1½ SM; increase LNAV Cats C/D visibility 1½ SM.

MALSR



**MISSED APPROACH:**  
Climb to 2000 direct  
REROY and hold.

ASOS  
120.775

LITTLE ROCK APP CON  
119.85 353.6

CLNC DE  
119.85

UNICOM  
123.0 (CTAF) **L**

