

WAAS CH <b>78099</b> <b>W15A</b>	APP CRS <b>153°</b>	Rwy Ldg TDZE Apt Elev	<b>9997</b> <b>1015</b> <b>1015</b>
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 15

ROBERT GRAY AAF (GRK)

RNP APCH - GPS.

▼

⚠

ASR/PAR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Circling NA west of Rwy 15-33.  
For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to 1 3⁄8 SM and LNAV Cats C/D/E visibility to 1 3⁄8 SM.  
# RVR 1800 authorized with the use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 2000 then climbing right turn to 3000 direct AGJ VORTAC and hold.

ATIS <b>124.9</b>	GRAY APP CON <b>120.075 323.15</b>	GRAY TOWER <b>120.75(CTAF) 285.5</b>	GND CON <b>121.8 279.5</b>	CLNC DEL <b>126.2 251.1</b>
----------------------	---------------------------------------	---	-------------------------------	--------------------------------

