




|  |                        |                             |   |
|--|------------------------|-----------------------------|---|
| WAAS<br>CH <b>42720</b><br><b>W01A</b> | APP CRS<br><b>008°</b> | Rwy Idg<br>TDZE<br>Apt Elev | <b>8199</b><br><b>729</b><br><b>742</b> |
|--|------------------------|-----------------------------|---|

RNAV (GPS) RWY 1

CHICAGO/ROCKFORD INTL (RFD)

|  |   |       |                                 |  |                          |
|--|---|-------|---------------------------------|--|--------------------------|
| RNP APCH - GPS.  |   | MALSR |                                 | MISSED APPROACH: Climb to 2500 direct WAGET and hold.  |                          |
| <br>ASR | For uncompensated Baro-VNAV systems, procedure NA below -16°C or above 54°C. For inop ALS, increase LNAV Cats C and D visibility to RVR 6000. *RVR 1800 authorized with use of FD or AP or HUD to DA. |       |                                 | <br> |                          |
| ATIS<br>127.6  | ROCKFORD APP CON<br>121.0 327.0   |       | ROCKFORD TOWER<br>118.1 290.375 |  | GND CON<br>121.9 290.375 |
|  |   |       | CLNC DEL<br>119.25              |  |                          |

