

WAAS CH <b>40009</b> <b>W24A</b>	APP CRS <b>236°</b>	Rwy Ldg TDZE Apt Elev	<b>9002</b> <b>66</b> <b>66</b>
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 24

FRANCIS S GABRESKI (F'OK)

RNP APCH - GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.  
Rwy 24 helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using HWV altimeter setting. Circling Rwy 15, 19 NA at night. When local altimeter setting not received, use HWV altimeter setting and increase LPV DA to 368 feet; increase LNAV/VNAV DA to 590 feet. Increase all MDAs 40 feet; and Circling visibility Cat C/D ¼ SM. For inop ALS, increase LPV all Cats visibility to ¾ SM, LNAV/VNAV visibility all Cats to 1 ¾ SM; LNAV Cats A/B visibility to 1 SM, Cats C/D visibility to 1 ¾ SM. For inop ALS when using HWV altimeter setting, increase LPV visibility all Cats to ¾ SM; LNAV Cats A/B visibility to 1 SM.



MISSED APPROACH:  
Climb to 2600 direct  
ZATBO and hold.

ASOS <b>119.925</b>	NEW YORK APP CON <b>125.975 343.65</b>	SUFFOLK TOWER ★ <b>125.3 (CTAF) 236.6</b>	GND CON <b>121.8 225.4</b>
------------------------	---	--	-------------------------------

