


WAAS CH 58329 W20B	APP CRS 203°	Rwy Ldg 11050 TDZE 439 Apt Elev 439
--	------------------------	--

RNAV (GPS) Y RWY 20R

FAIRBANKS INTL (FAI) (PAFA)

RNP APCH - GPS. -29°C Circling NA west of Rwy 2L-20R. Circling NA to Rwy 2W and 20W. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. # RVR 1800 authorized with use of FD or AP or HUD to DA.	MAISR MISSED APPROACH: Climb to 3000 direct JOTUG and hold.
--	--

ATIS 124.4	FAIRBANKS APP CON 125.35 363.2	FAIRBANKS TOWER 118.3 257.8	GND CON 121.9	CLNC DEL 127.6
----------------------	--	---------------------------------------	-------------------------	--------------------------



3000 ↑ JOTUG	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 74).			
RWY20R	HOVMO 5 NM to RWY20R	CIGNI 3400	ROPEE	ZUREP 4 NM Holding Pattern
1.6 NM	3.4 NM	4.1 NM	2.9 NM	2.9 NM
1.6 NM	3.4 NM	4.1 NM	2.9 NM	2.9 NM
CATEGORY	A	B	C	D
LPV DA#	639/24 200 (200-½)			
LNAV/VNAV DA	1148-2 709 (800-2)			
LNAV MDA	1020/24 581 (600-½)	1020-1¼ 581 (600-1¼)		
CIRCLING	1020-1 581 (600-1)	1020-1¾ 581 (600-¾)	1020-2 581 (600-2)	

