

WAAS CH <b>45502</b> <b>W15A</b>	APP CRS <b>154°</b>	Rwy Ldg <b>10702</b> TDZE <b>16</b> Apt Elev <b>17</b>
--	------------------------	--

RNAV (GPS) RWY 15  
CHENNAULT INTL (CWF)

RNP APCH - GPS

**ASR** **▼** Baro-VNAV and VDP NA when using Lake Charles Rgnl altimeter setting. For uncompensated Baro-VNAV systems, procedure NA below -15°C or above 54°C. When local altimeter setting not received, use Lake Charles Rgnl altimeter setting and increase LPV DA to 232 feet; increase LNAV/VNAV DA to 523 feet; increase all MDAs 20 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat D ¼ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to 1½ SM. For inop ALS when using Lake Charles Rgnl altimeter setting increase LNAV/VNAV visibility all Cats to 1½ SM.

MALSR



MISSED APPROACH: Climb to 2000 direct FERDU and hold.

ATIS <b>120.0</b>	LAKE CHARLES APP CON★ <b>119.8 282.3</b>	CHENNAULT TOWER★ <b>124.2 (CTAF) 0 290.4</b>	GND CON <b>121.65 275.8</b>	UNICOM <b>122.95</b>
----------------------	---	---	--------------------------------	-------------------------

