

WAAS	APP CRS	Rwy Ldg	10702
CH 65817	334°	TDZE	17
W33A		Apt Elev	17

RNAV (GPS) RWY 33

CHENNAULT INTL (CWF')

RNP APCH - GPS.

▼

Baro-VNAV and VDP NA when using Lake Charles Rgnl altimeter setting.

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

ASR

When local altimeter setting not received, use Lake Charles Rgnl altimeter setting and increase LPV DA to 233 feet; increase LNAV/VNAV DA to 510 feet and all visibilities ½ SM. Increase all MDAs 20 feet and LNAV visibility Cat C/D ½ SM.

MISSED APPROACH: Climb to 2000 direct CEVKU and hold.

ATIS	LAKE CHARLES APP CON ★	CHENNAULT TOWER ★	GND CON	UNICOM
120.0	119.8 282.3	124.2 (CTAF) 0 290.4	121.65 275.8	122.95

ELEV 17 D TDZE 17

2000	CEVKU			
		GOGNE	FERDU	4 NM Holding Pattern
	1.6 NM to RW33	1700	154°	6000
			334°	2000
		1700		GP 3.00°
				TCH 53
	1.6	3.5 NM	6 NM	
CATEGORY	A	B	C	D
LPV DA		217-¾	200 (200-¾)	
LNAV/VNAV DA		494-1¾	477 (500-1¾)	
LNAV MDA	580-1	563 (600-1)	580-1½	563 (600-1½)
CIRCLING	640-1	623 (700-1)	640-1¾	740-2¼
			623 (700-1¾)	723 (800-2¼)

LAKE CHARLES, LOUISIANA

Amdt 1B 29DEC22

30°13'N-93°09'W

CHENNAULT INTL (CWF')

RNAV (GPS) RWY 33

SC-4, 07 AUG 2025 to 04 SEP 2025

SC-4, 07 AUG 2025 to 04 SEP 2025