

WAAS CH 93932 W01A	APP CRS 007°	Rwy ldg TDZE Apt Elev	8001 1387 1409
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 1

BEECH FACTORY (BEC)

Baro-VNAV NA when using Wichita Dwight D Eisenhower Ntl altimeter setting.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Obtain local altimeter setting on CTAF; when not received, use Wichita Dwight D Eisenhower Ntl altimeter setting and increase all DA 36 feet and all MDA 40 feet; increase LPV all Cats and LNAV/VNAV all Cats visibility ½ mile, LNAV Cat C and D and Circling Cat C and D visibility ½ mile.

MISSED APPROACH:

Climb to 3000 direct DOLBE and hold.

AWOS-3PT 119.45	WICHITA APP CON 134.8 269.1	BEECH TOWER ★ 126.8 (CTAF) 0 313.6	GND CON 121.7	CLNC DEL 125.0 (When tower closed)	UNICOM 122.95
---------------------------	---------------------------------------	--	-------------------------	---	-------------------------

The main chart displays the RNAV (GPS) RWY 1 approach. Key features include:

- Waypoints and Altitudes:** ZOMED (3600), DENEY (3000), RAYON (3000), YOKUD (1511), JIMOK (3600), and DOLBE (3000).
- Distances:** 30 NM to ZOMED, 14 NM to DENEY, 6.2 NM to RAYON, 3.4 NM to YOKUD, and 1.6 NM to RW01.
- Angles:** 079°, 187°, 296°, and 29°.
- Missed Approach:** Climb to 3000 direct DOLBE and hold.

4 NM Holding Pattern				
GP 3.00° TCH 45				
*1920				
CATEGORY	A	B	C	D
LPV DA	1637-¾ 250 (300-¾)			
LNAV/VNAV DA	1688-1 301 (300-1)			
LNAV MDA	1780-1	393 (400-1)	1780-1½	393 (400-1½)
CIRCLING	1820-1 411 (500-1)	2120-1 711 (800-1)	2120-2 711 (800-2)	2120-2¼ 711 (800-2¼)

The inset chart shows the tower location (TWR 1437) and the runway (RW01). It includes a diagram of the approach path and the missed approach fix (DOLBE).

WICHITA, KANSAS
Amdt 1B 21AUG14

37°42'N-97°13'W

BEECH FACTORY (BEC)

RNAV (GPS) RWY 1

NC-2, 07 AUG 2025 to 04 SEP 2025

NC-2, 07 AUG 2025 to 04 SEP 2025