

WAAS CH <b>56425</b> <b>W29A</b>	APP CRS <b>294°</b>	Rwy Idg <b>4461</b> TDZE <b>97</b> Apt Elev <b>103</b>
--	------------------------	--

RNAV (GPS) RWY 29R  
ZAMPERINI FLD (TOA)

**⚠** For uncompensated Baro-VNAV systems, INAV/VNAV NA below 3°C (38°F) or above 54°C (130°F). Circling NA southwest of Rwy 11R/29L. DME/DME RNP-0.3 NA.

**⚠** For inop ALS, increase LPV alt Cats visibility to ½ SM. For inop ALS when using Los Angeles Intl altimeter setting, increase LPV alt Cats visibility to ¾ SM, INAV/VNAV alt Cats visibility to 2 SM, and LNAV Cat C visibility to 1½ SM. Baro-VNAV and VDP NA when using Los Angeles Intl altimeter setting. When local altimeter setting not received, except for operators with approved weather reporting service, use Los Angeles Intl setting: increase LPV DA to 391 feet and INAV/VNAV DA to 763 feet and all MDA 40 feet; increase LNAV/VNAV alt Cats visibility and LNAV Cat C visibility ½ SM.

MALSR



**MISSED APPROACH:** (Do not exceed 185 KIAS until ZANAN) Climb to 3000 direct ZANAN and on track 221° to INISH and hold, continue climb-in-hold to 3000.

ATIS <b>125.6</b>	SOCAL APP CON <b>124.3 363.2</b> (Rwys 11L, 11R) <b>127.2 269.6</b> (Rwys 29L, 29R)	TORRANCE TOWER* <b>133.075 257.8</b> (NORTH) <b>124.0</b> (CTAF) <b>0 257.8</b> (SOUTH)	GND CON <b>120.9</b>	UNICOM <b>122.95</b>
----------------------	---	---	-------------------------	-------------------------

