

WAAS

CH **82608**

**W17A**

APP CRS

**167°**

Rwy ldg

**5002**

TDZE

**294**

Apt Elev

**295**

**RNAV (GPS) RWY 17**

TACOMA NARROWS (TIW)

RNP APCH.

▼

VDP NA with McChord Fld altimeter setting. For inoperative MALS, increase LPV all Cats visibility to 1 1/2 mile. Circling NA east of Rwy 17/35.

▲

Baro-VNAV NA when using McChord Fld altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). When local altimeter setting not received, use McChord Fld altimeter setting and increase all DA 25 feet, all MDA 40 feet, and increase LPV all Cats visibility 1/2 mile.

MALS

MISSED APPROACH: Climb to 4000 direct WAPGI and right turn via 285° track to CARRO and hold, continue climb-in-hold to 4000.

ATIS <b>124.05</b>	SEATTLE APP CON <b>120.1 290.9</b>	TACOMA TOWER ★ <b>118.5 (CTAF) 0 253.5</b>	GND CON <b>121.8</b>	UNICOM <b>122.95</b>
-----------------------	---------------------------------------	---	-------------------------	-------------------------

4000

WAPGI

CARRO

TETGE

FAVDU

Procedure Turn NA

\* LNAV only.

\* 2 NM to RW17

2 NM

3.1 NM

6.2 NM

GP 3.00° TCH 52

CATEGORY	A	B	C	D
LPV DA		638-5/8	344 (400-5/8)	
LNAV/VNAV DA		992-2	698 (700-2)	
LNAV MDA	980-1/2	686 (700-1/2)	980-1 1/2	686 (700-1 1/2)
CIRCLING	980-1	685 (700-1)	980-2 685 (700-2)	980-2 1/4 685 (700-2 1/4)

TACOMA, WASHINGTON

Orig-C 08OCT20

47°16'N-122°35'W

TACOMA NARROWS (TIW)

**RNAV (GPS) RWY 17**