

LOC/DME I-ANE
111.15
Chan **48** (Y)

APP CRS
269°

Rwy Idg **5000**
TDZE **910**
Apt Elev **912**

ILS or LOC RWY 27

ANOKA COUNTY/BLAINE (JANES FLD) (A.N.E.)

DME required. RADAR required for procedure entry at BLAYN.

▼

⚠

VDP NA when using Crystal altimeter setting. When local altimeter setting not received, use Crystal altimeter setting and increase S-ILS 27 DA to 1131 feet; increase all MDAs 40 feet and S-LOC 27 visibility Cat C/D ¼ SM, and Circling visibility Cat D ¼ SM. For inop ALS when using Crystal altimeter setting, increase S-LOC 27 Cat C/D visibility to 1 ½ SM.

MALSR

MISSED APPROACH: Climb to 2700 direct GEP VORTAC and hold, continue climb-in-hold to 2700.

ATIS 120.625	MINNEAPOLIS APP CON 126.5 335.65	ANOKA TOWER★ 132.4 (CTAF) 0	GND CON 121.85	CLNC DEL 121.3	CLNC DEL 121.85 (When twr closed)	UNICOM 122.95
------------------------	--	--	--------------------------	--------------------------	--	-------------------------

MISSED APCH FIX

GOPHER
GEP
117.3
Chan 120

R-264 084° 264°

GOPHER
117.3 GEP
Chan 120

Δ1530

LOCALIZER
I-ANE
111.15
Chan 48(Y)

2438

KOGGE I-ANE 3.6

BOKYA I-ANE 6.2

LR-079

2600

269° (10.5)

089°

JUDAL I-ANE 16.7

3100 to JUDAL 276° hdg (1.9) and 269° (6)

(IAF) STILS GEP 30.9

(IAF) BLAYN GEP 23

3100

GEP 23

3100

3500

MSA GEP 2.5 NM

ELEV 912	TDZE 910
81	269°
4855 X 100	5000 X 100
6	36
964	
HIRL Rwy 9-27	
MIRL Rwy 18-36	
REIL Rwys 9, 18, and 36	
FAF to MAP 5.2 NM	
Knots 60 90 120 150 180	
Min:Sec 5:12 3:28 2:36 2:05 1:44	
2700	Use I-ANE DME when on the localizer course.
GEP	JUDAL I-ANE 16.7
I-ANE 1	BOKYA I-ANE 6.2
I-ANE 2.2	KOGGE I-ANE 3.6
1780	2600
1.2 NM	1.4 NM
2.6 NM	10.5 NM
3100	GS 3.00° TCH 49
CATEGORY	A B C D
S-ILS 27	1110-½ 200 (200-½)
S-LOC 27	1340-½ 430 (500-½) 1340-¾ 430 (500-¾)
CIRCLING	1400-1 488 (500-1) 1420-1½ 508 (600-1½) 1580-2 668 (700-2)

MINNEAPOLIS, MINNESOTA

ANOKA COUNTY/BLAINE (JANES FLD) (A.N.E.)

ILS or LOC RWY 27

Amdt 1 08SEP22

45°09'N-93°13'W

NC-1, 07 AUG 2025 to 04 SEP 2025

NC-1, 07 AUG 2025 to 04 SEP 2025