

APP CRS  
**179°**

Rwy Idg  
TDZE  
Apt Elev

**4855**  
**912**  
**912**

RNAV (GPS) RWY 18

ANOKA COUNTY/BLAINE (JANES FLD) (A.N.E.)

RNP APCH - GPS.

When local altimeter setting not received, use Crystal altimeter setting and increase all MDA 40 feet and Circling Cat D visibility ¼ SM.  
VDP NA when using Crystal altimeter setting.

MISSED APPROACH: Climbing left turn to 2600 direct RUNRR and hold.

ATIS <b>120.625</b>	MINNEAPOLIS APP CON <b>126.5 335.65</b>	ANOKA TOWER★ <b>132.4 (CTAF) 0</b>	GND CON <b>121.85</b>	CLNC DEL <b>121.3</b>	CLNC DEL <b>121.85</b> (When twr closed)	UNICOM <b>122.95</b>
------------------------	--	---------------------------------------	--------------------------	--------------------------	--	-------------------------

2600

RUNRR

1.3 NM to RWY 18

DOZXU

179°

359°

2600

4 NM Holding Pattern

1.3 NM

2.3 NM

6.1 NM

CATEGORY	A	B	C	D
LNNAV MDA	1380-1	468 (500-1)	1380-1⅓	468 (500-1⅓)
CIRCLING	1400-1	488 (500-1)	1460-1½ 548 (600-1½)	1580-2 668 (700-2)

ELEV 912

TDZE 912

179°

81

4855 X 100

5000 X 100

TWR

36

964

HIRL Rwy 9-27 0

MIRL Rwy 18-36 0

REIL Rws 9, 18 and 36 0

MINNEAPOLIS, MINNESOTA

ANOKA COUNTY/BLAINE (JANES FLD) (A.N.E.)

Orig-G 03NOV22

45°09'N-93°13'W

RNAV (GPS) RWY 18