

MAYNR THREE DEPARTURE (RNAV)

**TOP ALTITUDE:
ASSIGNED BY ATC**



RNAV 1 - DME/DME/IRU or GPS.

From SLIPT to MAXIM: RNAV 1 - GPS.

From SLIPT to CANOA: RNAV 1 - GPS.

RADAR required for non-GPS equipped aircraft.

RADAR required.

TAKEOFF MINIMUMS

Rwy 9L: Standard with minimum climb of 500'/NM to 1300.

Rwy 9R: Standard with minimum climb of 500'/NM to 1500.

Rwy 13: Standard with minimum climb of 500'/NM to 1800.

Rwy 27L: Standard with minimum climb of 500'/NM to 1900.

Rwy Z/K: Standard with minimum climb of 500'/NM to 1700.
Rwy 21: Standard with minimum climb of 500'/NM to 1400.

RWY 31: Standard with minimum climb of 300 / NM to 1400.

NOTE: Jet aircraft only.

NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.

MSA TMB 25 NM

291

MIAMI DEP CON

125.5 354.1

ATIS
1940

CLINIC DEL 24.0

133.0 CINC DEL

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SE-3, 07 AUG 2025 to 04 SEP 2025

MAYNR THREE DEPARTURE (RNAV)

(MAYNR3.MAYNR) 31OCT24

MIAMI, FLORIDA
MIAMI EXEC (TMB)

