

WAAS CH <b>50314</b> <b>W07A</b>	APP CRS <b>066°</b>	Rwy Idg TDZE <b>742</b> Apt Elev <b>742</b>
--	------------------------	---



RNAV (GPS) RWY 7L

KENOSHA RGNL (ENW)

RNP APCH - GPS.			MALSR	MISSED APPROACH: Climb to 2500 then climbing left turn to 3000 direct DIKHU and hold.	
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div></div> <div>Circling Rwy 7R, 1.5 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to 1½ SM.</div>					
ATIS 127.175	MILWAUKEE APP CON 135.875 317.725	KENOSHA TOWER ★ 118.6 (CTAF) 0 353.6	GND CON 121.875	CLNC DEL 121.875	CLNC DEL 118.6 (When twr closed)

UNICOM

122.95



CATEGORY	A	B	C	D
LPV DA		942-½	200 (200-½)	
LNAV/VNAV DA		1181-¾	439 (500-¾)	
LNAV MDA	1160-½	418 (500-½)	1160-¾	418 (500-¾)
CIRCLING	1200-1 458 (500-1)	1340-1 598 (600-1)	1400-1¾ 658 (700-1¾)	1440-2¼ 698 (700-2¼)

