

LOC/DME I-HEW 110.5 Chan 42	APP CRS 168°	Rwy Idg TDZE 152 Apt Elev 152	6002
---	------------------------	---	-------------



LOC RWY 17R
DAVID WAYNE HOOKS MEML (DWH)

RADAR required for procedure entry.

When local altimeter setting not received, use George Bush Intcnl/Houston altimeter setting and increase all MDA 40 feet; increase S-LOC 17R Cts C/D visibility ½ mile. Circling NA to Rwy 17W and 35W. Rwy 17R helicopter visibility reduction below ¾ SM NA. Circling Rwy 35R NA at night.

MISSED APPROACH: Climb to 1200 then climbing right turn to 2000 on heading 325° and IAH VORTAC R-293 to TNV VOR/DME and hold.

ATIS 128.375	HOUSTON APP CON 119.7 281.4	HOOKS TOWER★ 127.4 354.1 EAST 118.4 (CTAF) 354.1 WEST	GND CON 121.8 239.0	CLNC DEL 119.45	UNICOM 122.95
------------------------	---------------------------------------	---	-------------------------------	---------------------------	-------------------------



Visual Segment - Obstacles.				1200	2000	IAH R-293	TNV
TUKII INT I-HEW 14.3 RADAR				2000	1800	1.1	
FLIKA INT I-HEW 6 RADAR							
I-HEW 1.1							
8.3 NM				4.9 NM			
CATEGORY	A		B		C		D
S-LOC 17R	640-1		488 (500-1)		640-1½		488 (500-1½)
CIRCLING	640-1		660-1		680-1½		780-2
	488 (500-1)		508 (600-1)		528 (600-1½)		628 (700-2)