

WAAS CH 45533 W28A	APP CRS 282°	Rwy Idg TDZE 941 Apt Elev 941
--	------------------------	---

RNAV (GPS) RWY 28

BROOKS FLD (RMY)

RNP APCH - GPS.

▼


Rwy 28 helicopter visibility reduction below ¾ SM NA. Circling Rwy 10 NA at night.

▲

When local altimeter setting not received, use BTL altimeter setting: increase all MDAs 40 feet and increase LP and LNAV Cat C visibility ½ SM and Circling Cat C visibility ¼ SM. VDP NA with BTL altimeter setting.

MISSED APPROACH: Climb to 1500 then climbing left turn to 3100 direct AWSOF and hold.

AWOS-3 120.025	GREAT LAKES APP CON ★ 119.2 239.25	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



ELEV 941

TDZE 941

1500

3100

AWSOF

VGSI and descent angles not coincident (VGSI Angle 4.00/TCH 37).

4 NM Holding Pattern

1900

2600

6000

3100

0.8 NM to RW28

2.1 NM

2.2 NM

7 NM

CATEGORY	A	B	C	D
LP MDA	1320-1 379 (400-1)			NA
LNAV MDA	1320-1 379 (400-1)			NA
CIRCLING	1440-1 499 (500-1)		1660-2 719 (800-2)	NA

MIRL Rwy 10-28 0