

WAAS CH <b>90203</b> <b>W13A</b>	APP CRS <b>130°</b>	Rwy Idg TDZE <b>2032</b> Apt Elev <b>2034</b>
--	------------------------	---

RNAV (GPS) RWY 13

THE O'NEILL MUNI-JOHN L BAKER FLD (ONL)

⚠

Baro-VNAV NA when using Evelyn Sharp Fld altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Evelyn Sharp Fld altimeter setting and increase LPV DA to 2433 feet, LNAV/VNAV DA to 2505 feet; increase all MDAs 140 feet and visibility Cat C ½ SM. VDP NA when using Evelyn Sharp Fld altimeter setting. Night landing: Rwy 4, 22 NA.

MISSED APPROACH:

Climb to 4000 direct AFSIC and hold.

AWOS-3 <b>121.125</b>	MINNEAPOLIS CENTER <b>128.0 257.95</b>	UNICOM <b>122.8 (CTAF) 0</b>
--------------------------	---	---------------------------------

Chart details: The main chart shows the RNAV (GPS) RWY 13 approach. Key features include:

- Waypoints:** SUXXGY (IAF), AKIGE (IF/IAF), IMUYE (FAF), and the final approach to RWY 13.
- Altitudes:** 4000 ft at SUXXGY, 3700 ft at AKIGE, 3100 ft at IMUYE, and 2109 ft at RWY 13.
- Angles:** 130° heading, 310° turn angles, and 061°/040° angles for the initial approach.
- Obstacles:** Lake Andes MOA, O'Neill MOA, and various terrain elevations (e.g., 2569, 2161, 2489).
- Navigation Aids:** AFSIC, AFSIC, and AFSIC.
- Procedure:** Procedure NA for arrivals at ONL VORTAC via V71 southeast bound.

ELEV 2034	TDZE 2032
-----------	-----------

Inset chart details: This inset chart shows the REIL (Runway End Identifier Lights) and MIRL (Medium Intensity Runway Lights) for RWY 13 and 31. Key features include:

- REIL:** RWY 13 and 31.
- MIRL:** RWY 13-31.
- Dimensions:** 4408 x 75 and 3200 x 60.
- Angles:** 130° heading.

5 NM Holding Pattern				AKIGE		IMUYE		4000		AFSIC		
GP 3.00°				310°		130°		130°		*1.1 NM to RWY13		
TCH 39				3700		3700		3700		*LNAV only.		
6 NM				3.9 NM		1.1 NM		1.1 NM		1.1 NM		
CATEGORY	A		B		C		D					
LPV DA	2308-1		276 (300-1)				NA					
LNAV/VNAV DA	2380-1¼		348 (400-1¼)				NA					
LNAV MDA	2420-1		388 (400-1)				NA					
CIRCLING	2600-1		566 (600-1)		2680-1¾		646 (700-1¾)				NA	

O'NEILL, NEBRASKA

Amcl 1C 07OCT21

THE O'NEILL MUNI-JOHN L BAKER FLD (ONL)

42°28'N-98°41'W

RNAV (GPS) RWY 13