

LOC I-JAX
110.7

APP CRS
077°

Rwy Idg **10000**
TDZE **30**
Apt Elev **30**

ILS Y RWY 8 (CAT II & III)
JACKSONVILLE INTL (JAX)

ALSF-2

MISSED APPROACH: Climb to 1000 then climbing left turn to 3000 on heading 250° and on CRG VORTAC R-290 to MONIA INT/CRG 29.2 DME/RADAR and hold.

D-ATIS
125.85

JACKSONVILLE APP CON
119.0 269.9

JACKSONVILLE TOWER
118.3 317.7

GND CON
121.9 348.6

CLNC DEL
119.5 290.275

CPDLC

The main chart displays the ILS Y RWY 8 approach. Key features include:

- Localizer:** 110.7 I-JAX, 3-dot-dash pattern.
- Monia CRG:** 29.2, 110.7, 290° heading.
- Libby CRG:** 20.5, 190° heading.
- Craig CRG:** 114.5, 116.9, 92° heading.
- Navigation Aids:** 109.8 SSI Chan 35, 116.2 GNV Chan 109, 1090 tower.
- Obstacles:** A276, A451, A280, A1041.
- Procedure:** NA for arrival on CRG VORTAC airway radials 290 CW 336.

This diagram shows the final approach segment with altitudes and headings:

- 2000 ft at 257° heading.
- 1861 ft at 077° heading.
- 1900 ft at 1861 ft.
- 5.6 NM distance to the runway.
- 1046 ft at the runway threshold.

CATEGORY	A	B	C	D
S-ILS 8	CAT II RA 100/12 100 DA 130			
S-ILS 8	CAT IIIa RVR 06			

CATEGORY II & III ILS - SPECIAL AIRCREW & AIRCRAFT CERTIFICATION REQUIRED

REIL Rwy 32
TDZ/CL Rws 8, 14, and 26
HIRL Rws 8-26 and 14-32

JACKSONVILLE, FLORIDA

Amdt 14 03NOV22

JACKSONVILLE INTL (JAX)

30°30'N-81°41'W

ILS Y RWY 8 (CAT II & III)