

WAAS CH 86801 W03A	APP CRS 026°	Rwy Idg 5502 TDZE 315 Apt Elev 315
--	------------------------	---

RNAV (GPS) RWY 3

SIKESTON MEML MUNI (SIK)



RNP APCH.

NA

Rwy 3 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using Cape Girardeau altimeter setting. For uncompensated Baro-VNAV systems, procedure NA below -15°C or above 54°C. When local altimeter setting not received, use Cape Girardeau altimeter setting and increase all DA 49 feet and all MDA 60 feet. Increase LNAV and Circling Cat C/D visibility ¼ SM.

MISSED APPROACH: Climb to 2200 direct IBEFY and hold.

AWOS-3 119.175	MEMPHIS CENTER 133.65 292.15	UNICOM 122.8 (CTAF)
--------------------------	--	-------------------------------



4 NM Holding Pattern		CUXID	GAYEV	2200 IBEFY
6000 ← 206°		2000	2000	YEKUD 1.6 NM to RW03
2000 → 026°		2000	2000	*LNAV only
GP 3.00°				RW03
TCH 45				*860
		6.8 NM	3.6 NM	1.6 NM
CATEGORY	A	B	C	D
LPV DA	629-1 314 (400-1)			
LNAV/VNAV DA	769-1½ 454 (500-1½)			
LNAV MDA	720-1	405 (500-1)	720-1½	405 (500-1½)
CIRCLING	840-1 525 (600-1)	860-1 545 (600-1)	1080-2¼ 765 (800-2¼)	1160-2¾ 845 (900-2¾)

