

WAAS

CH **56304**

W16A

APP CRS

165°

Rwy Idg

4400

TDZE

1055

Apt Elev

1060

RNAV (GPS) RWY 16

ROSEAU MUNI/RUDY BILLBERG FLD (R.O.X)

RNP APCH - GPS.

⚠

Circling NA to Rwy 6 and 24. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LNAV/VNAV visibility to 7/8 SM. Inop table does not apply to LPV all Cats.

MALSF

⚠

MISSED APPROACH: Climb to 2800 direct ACEBO and hold.

AWOS-3 118.075	MINNEAPOLIS CENTER 134.75 251.1	UNICOM 122.8 (CTAF) 0
--------------------------	---	--

The main chart displays the RNAV (GPS) RWY 16 approach. Key features include:

- Initial Approach:** 30 NM to BADYA (NoPT) at 2800 ft, 074° heading, 255° turn.
- Intermediate Approach:** 5 NM to (IF/IAF) BADYA at 2800 ft, 165° heading, 345° turn.
- Final Approach:** 1.9 NM to RW16 at 1700 ft, 165° heading, 345° turn.
- Altitudes:** 2800 ft (initial), 2700 ft (intermediate), 1700 ft (final), 1514 ft (MSL), 1243 ft (AGL), 1614 ft (AGL).
- Navigation Aids:** MALSF, ACEBO, KOTCH, EASEY, BADYA, CATPI, BATBY.
- Obstacles:** 1514 MSL, 1243 AGL, 1614 AGL.
- Missed Approach:** Climb to 2800 ft, direct ACEBO and hold.

MISSED APCH FIX		ELEV 1060		TDZE 1055	
ACEBO		2800		ACEBO	
5 NM Holding Pattern		6000		2800	
GP 3.00°		2700		1700	
TCH 44		5.9 NM		3.1 NM	
CATEGORY		A		B	
LPV DA		1255-3/4		200 (200-3/4)	
LNAV/VNAV DA		1330-3/4		275 (300-3/4)	
LNAV MDA		1420-3/4		365 (400-3/4)	
CIRCLING		1600-1		540 (600-1)	
		1840-2 1/4		780 (800-2 1/4)	
		1840-2 1/2		780 (800-2 1/2)	

4400 X 75

2097 X 250

34

MIRL Rwy 16-34

REIL Rwy 34

ROSEAU, MINNESOTA

Amtd 1 03NOV22

ROSEAU MUNI/RUDY BILLBERG FLD (R.O.X)

48°51'N-95°42'W

RNAV (GPS) RWY 16