

WAAS
CH **63124**
W05A

APP CRS
050°

Rwy Idg
TDZE **847**
Apt Elev **847**

RNAV (GPS) RWY 5

SHELBY-CLEVELAND COUNTY RGNL (EHO)

▼

⚠

Baro-VNAV NA when using Charlotte altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 38°C. Rwy 5 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Charlotte altimeter setting and increase all DA 88 feet and all MDA 100 feet; increase LPV all Cats visibility ½ SM and LNAV/VNAV all Cats, LNAV Cat C/D visibility ¼ SM.

MISSED APPROACH: Climb to 4000 direct JIRUL and on track 046° to LINCO and hold.

AWOS-3 118.425	CHARLOTTE APP CON 120.05 257.2	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------

4 NM Holding Pattern	ZISUG	UPCEG	JIRUL	LINCO
3000	3000	3000	4000	tr 046°
GP 3.00° TCH 41	3000	YIGUG 2.1 NM to RWY05	* LNAV only.	RWY05
230°	050°	050°		
6.1 NM	4.6 NM	2.1 NM		

CATEGORY	A	B	C	D
LPV DA	1097-1 250 (300-1)			
LNAV/VNAV DA	1173-1½ 326 (400-1½)			
LNAV MDA	1240-1 393 (400-1)		1240-1½ 393 (400-1½)	

SHELBY, NORTH CAROLINA

Amdt 2B 15AUG19

35°15'N-81°36'W

SHELBY-CLEVELAND COUNTY RGNL (EHO)

RNAV (GPS) RWY 5