

APP CRS

055°

Rwy Idg

6000

TDZE

670

Apt Elev

681

RNAV (GPS) RWY 6

MAURY COUNTY RGNL (MRC)

⚠

⚠

DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. When local altimeter setting not received, use Nashville Intl altimeter setting; increase all MDA 120 feet and increase LNAV Cat B visibility ¼ SM, Cats C and D visibility ½ SM, increase Circling Cat C visibility ½ SM.

MISSED APPROACH:

Climb to 3000 direct URSAW and hold.

AWOS-3 128.625	MEMPHIS CENTER 125.85 379.25	UNICOM 122.8 (CTAF) 0
-------------------	---------------------------------	--------------------------

The main chart displays the RNAV (GPS) RWY 6 approach. Key features include:

- Initial Descent:** From 3000 ft, a 145° turn leads to IJAPU, followed by a 235° turn to 3000 ft.
- Intermediate Descent:** From 3000 ft, a 145° turn leads to CEMVU, followed by a 235° turn to 3000 ft.
- Final Descent:** From 3000 ft, a 145° turn leads to DOXGU, followed by a 235° turn to 3000 ft.
- Final Approach:** From 3000 ft, a 145° turn leads to ALWUB, followed by a 235° turn to 3000 ft.
- Final Descent:** From 3000 ft, a 145° turn leads to RW06, followed by a 235° turn to 3000 ft.
- Altitudes:** 3000 ft, 3200 ft, 2500 ft, 2000 ft, 1449 ft, 1216 ft, 1075 ft, 1042 ft, 875± ft, 1335 ft.
- Navigation Aids:** IJAPU, CEMVU, DOXGU, ALWUB, RW06, URSAW.
- Obstacles:** 1199, 729, 1075, 1042, 875±, 1335, 1449.
- Distance Markers:** 4 NM, 30 NM to IJAPU, 30 NM to DOXGU, 26 NM to CEMVU (NoPT).

4 NM Holding Pattern

CEMVU

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 42).

3000

URSAW

235°

055°

055°

2500

3.05° TCH 40

6.1 NM

5.6 NM

RW06

055°

0.5% Up

0.4% Up

191 X 25

35

6000 X 100

1

CATEGORY	A	B	C	D
LNAV MDA	1340-1	670 (700-1)	1340-1¾ 670 (700-1¾)	1340-2 670 (700-2)
CIRCLING	1340-1 659 (700-1)	1360-1 679 (700-1)	1380-2 699 (700-2)	1620-3 939 (1000-3)

MIRL Rwy 6-24

REIL Rwy 6

REIL Rwy 24 0

COLUMBIA/MOUNT PLEASANT, TENNESSEE

MAURY COUNTY RGNL (MRC)

Orig-A 09SEP21

35°33'N-87°11'W

RNAV (GPS) RWY 6