LOC RWY 21

HILTON HEAD (HXD)

LOC/DME I-HXD	APP CRS	Rwy Ldg	4597
111.3	213°	TDZE	18
Chan 50		Apt Elev	19

NA

Rwy 21 helicopter visibility reduction below 3/4 SM NA. DME required.

MISSED APPROACH: Climb to 800 then climbing right turn to 2000 on SAV R-085 to SELER/SAV 21.5 DME and hold, continue climb-in-hold to 2000.

ATIS	SAVANNAH APP CON ★	HILTON HEAD TOWER ★	GND CON	CLNC DEL	CLNC DEL
121.4	125.3 371.875	118.975 (CTAF) L	121.1	121.1	123.85 (When twr closed)

RADAR REQUIRED

033°

(IF) ZEXUN I-HXD 13.5

1800

213° (7.4)

JAAMM I-HXD 6.1

WOVIN I-HXD 3

169

150

154 ±

206

849

SELER SAV 21.5

085°

265°

R-085

ALTERNATE MISSED APCH FIX

113.5 CHS

R-219

Chan 82

039°

219°

TYBEE CHS 76.1

SAVANNAH 115.95 SAV Chan 106 (Y)

MSA SAV 25 NM

2600

LOCALIZER 111.3 I-HXD Chan 50

ELEV 19 D TDZE 18

213°

21

TWR

5000 X 100

3

MIRL Rwy 3-21 L

REIL Rwys 3 and 21 L

800 | 2000 SAV R-085 | SELER SAV 21.5

JAAMM I-HXD 6.1

ZEXUN I-HXD 13.5

WOVIN I-HXD 3

I-HXD 1.9

I-HXD 0.8

213° 1800

1800

3.13°

760 TCH 40

1.1 NM 1.1 NM 3.1 NM 7.4 NM

CATEGORY	A	B	C	D
S-21	400-1 382 (400-1)		400-1⅛	382 (400-1⅛)
C CIRCLING	480-1 461 (500-1)	520-1 501 (600-1)	520-1½ 501 (600-1½)	580-2 561 (600-2)

SE-2, 07 AUG 2025 to 04 SEP 2025
SE-2, 07 AUG 2025 to 04 SEP 2025