



WAAS CH <b>70743</b> <b>W24A</b>	APP CRS <b>235°</b>	Rwy Idg TDZE Apt Elev	<b>3693</b> <b>435</b> <b>435</b>
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 24  
NEW GARDEN (N57)

RNP APCH: ▼ ▲ NA Rwy 24 helicopter visibility reduction below 1 SM NA. Obtain local altimeter setting on CTAF; when local altimeter not received, use New Castle altimeter setting and increase all MDA 80 feet. Increase LP Cat C visibility 3⁄8 SM, LNAV Cat C visibility 1⁄4 SM and Circling Cat C visibility 1⁄4 SM.		MISSED APPROACH: Climb to 2200 direct DELFA and hold.
PHILADELPHIA APP CON <b>124.35 319.15</b>	CLNC DEL <b>125.6</b>	UNICOM <b>123.05 (CTAF) 0</b>



RWY 24		ENUKE	ZEYNU	4 NM Holding Pattern
2200		2000	235°	055° 6000 2200
4.8 NM		5 NM		
CATEGORY	A	B	C	D
LP MDA	880-1	445 (500-1)	880-1 1⁄8 445 (500-1 1⁄8)	NA
LNAV MDA	900-1	465 (500-1)	900-1 3⁄8 465 (500-1 3⁄8)	NA
CIRCLING	960-1	525 (600-1)	960-1 1⁄2 525 (600-1 1⁄2)	NA