

|  |                        |  |
|--|------------------------|--|
| WAAS<br>CH <b>86735</b><br><b>W36A</b> | APP CRS<br><b>001°</b> | Rwy Ldg<br>TDZE<br>Apt Elev<br><b>6000</b><br><b>401</b><br><b>402</b> |
|--|------------------------|--|

RNAV (GPS) RWY 36

OLIVE BRANCH/TAYLOR FLD (OLV)



▼

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Memphis Int'l altimeter setting and increase all DA 32 feet and all MDA 40 feet; increase LPV and LNAV/VNAV all Cats and LNAV Cats C and D and Circling Cats C and D visibility ¼ mile. VDP and Baro-VNAV NA with Memphis Int'l altimeter setting. Rwy 36 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:  
Climb to 1500 then  
climbing right turn  
to 2000 direct  
DOCAP and hold.

|                        |                                       |   |                         |                          |   |                         |
|------------------------|---------------------------------------|---|-------------------------|--------------------------|---|-------------------------|
| ATIS<br><b>119.925</b> | MEMPHIS APP CON<br><b>125.8 338.3</b> | OLIVE BRANCH TOWER ★<br><b>125.275 (CTAF) 0</b> | GND CON<br><b>121.2</b> | CLNC DEL<br><b>121.2</b> | CLNC DEL<br><b>121.3</b><br>(When twr closed) | UNICOM<br><b>122.95</b> |
|------------------------|---------------------------------------|---|-------------------------|--------------------------|---|-------------------------|



|              |        |                 |  |                         |                      |                 |
|--------------|--------|-----------------|--|-------------------------|----------------------|-----------------|
| 1500         | 2000   | DOCAP           | VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 31). |                         |                      |                 |
| *LNAV only   |        | *1.8 NM to RW36 | CICAL 2000   | DOCAP                   | 4 NM Holding Pattern |                 |
| RW36         |        | 1.8 NM          | 3.1 NM   | 7 NM                    | 181° → 2000          | GP 3.00° TCH 45 |
| CATEGORY     | A      | B               | C  | D                       |                      |                 |
| LPV DA       | 709-1  |                 | 308 (400-1)  |                         |                      |                 |
| LNAV/VNAV DA | 915-1¾ |                 | 514 (600-1¾)   |                         |                      |                 |
| LNAV MDA     | 1000-1 | 599 (600-1)     | 1000-1¾  | 599 (600-1¾)            |                      |                 |
| CIRCLING     | 1060-1 | 658 (700-1)     | 1060-1¾<br>658 (700-1¾)  | 1200-2½<br>798 (800-2½) |                      |                 |