

WAAS

CH 42810

W05A

APP CRS

045°

Rwy Idg

5000

TDZE

35

Apt Elev

37

RNAV (GPS) RWY 5

WASHINGTON-WARREN (OCW)

RNP APCH-GPS.

⚠

Circling Rwy 17 NA at night. Baro-VNAV and VDP NA when using Greenville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.

⚠

Rwy 5 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Greenville altimeter setting: increase LPV DA to 484 feet and visibility ¼ SM, and LNAV/VNAV DA to 519 feet; increase all MDAs 60 feet and visibility LNAV Cat C/D ¼ SM.

MISSED APPROACH:

Climb to 2600 direct HALAX and hold.

AWOS-3 120.175	CHERRY POINT APP CON 119.35 377.175	UNICOM 122.7 (CTAF) 0
-------------------	--	--------------------------

COULD					RWY 05				
2000					2600				
GP 3.00°					HALAX				
TCH 40									
6.1 NM					3.2 NM				
1.5 NM									
CATEGORY	A		B		C		D		
LPV DA			442-1⅞		407 (500-1⅞)				
LNAV/VNAV DA			477-1⅜		442 (500-1⅜)				
LNAV MDA	560-1		525 (600-1)		560-1½		525 (600-1½)		
CIRCLING	560-1		523 (600-1)		640-1¾		780-2½		
					603 (700-1¾)		743 (800-2½)		

ELEV 37

TDZE 35

REIL Rwy 5 and 23 0

MIRL Rws 5-23 0

WASHINGTON, NORTH CAROLINA

Amdt 1C 12AUG21

35°34'N-77°03'W

WASHINGTON-WARREN (OCW)

RNAV (GPS) RWY 5