

WAAS CH 45737 W16A	APP CRS 155°	Rwy Idg TDZE Apt Elev	4997 82 83
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 16


DE QUINCY INDUSTRIAL AIRPARK (5R8)

Baro-VNAV NA when using Sulphur altimeter setting. DME/DME RNP-0.3 NA.

When local altimeter setting not received, use Sulphur altimeter setting and increase all DA 55 feet and MDA 60 feet, increase LPV visibility all Cats ¼, LNAV/VNAV all Cats ¼ and LNAV and Circling Cat C visibility ¼ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). Helicopter visibility reduction below 1 SM NA. Night landing: Rwy 16 NA.

MISSED APPROACH: Climb to 2000 direct QUNKE and on track 193° to STRUT and hold.

AWOS-3PT 121.2	LAKE CHARLES APP CON * 119.35 282.3	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



4 NM Holding Pattern FEPRO		DEQHU	2000	QUNKE	tr 193°	STRUT
1700 ← 335°		155° →	1700	ZEVS 2.1 NM to RW16	*LNAV only	
GP 3.00° TCH 50		1700	*800		RW16	
6.1 NM		2.8 NM	2.1 NM			
CATEGORY	A	B	C	D		
LPV DA	365-1		283 (300-1)		NA	
LNAV/VNAV DA	799-2½		717 (800-2½)		NA	
LNAV MDA	700-1		618 (700-1)		700-1¾ 618 (700-1¾)	
CIRCLING	700-1 617 (700-1)		740-1 657 (700-1)		740-1¾ 657 (700-1¾)	