



APP CRS	Rwy Idg	5020
175°	TDZE	806
	Apt Elev	806

RNAV (GPS) RWY 17

MIAMI RGNL (MIO)

RNP APCH.	ODALS	MISSED APPROACH: Climb to 2500 direct LUCGY and hold.
▼ Baro-VNAV and VDP NA when using Grove altimeter setting. ▲ Rwy 17 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Grove altimeter setting.		

AWOS-3PT 119.675	KANSAS CITY CENTER 128.6 282.325	UNICOM 122.8 (CTAF) 0
---------------------	-------------------------------------	--------------------------



4 NM Holding Pattern				VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 42).	2500	LUCGY
				* LNAV only		
				* 1.5 NM to RWY 17		
				GP 3.00° TCH 31		
				5.9 NM 3.7 NM 1.5 NM		
CATEGORY	A	B	C	D		
LNAV/VNAV DA	1206-1 ¼ 400 (400-1 ½)				NA	
LNAV MDA	1320-1 514 (600-1)		1320-1 ¾ 514 (600-1 ¾)		NA	
CIRCLING	1320-1 514 (600-1)		1460-1 ¾ 654 (700-1 ¾)		NA	