

WAAS CH 45805 W35B	APP CRS 356°	Rwy Ldg 13400 TDZE 564 Apt Elev 607	RNAV (GPS) RWY 35L DALLAS-FORT WORTH INTL (DFW)
--	------------------------	--	---

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C (25°F) or above 54°C (130°F). Simultaneous approach authorized with Rwy 36L/R and Rwy 35R. DME/DME RNP-0.3 NA. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

MALSR

MISSED APPROACH:

Climb to 3000 direct BBAKR and on track 357° to BOSSI and hold.

D-ATIS ARR 123.775 DEP 135.925	LONE STAR APP CON 127.075	DFW TOWER 126.55 127.5 EAST 124.15 134.9 WEST	GND CON 121.65 121.8 EAST 121.85 WEST	CLNC DEL 128.25	CPDLC
--	-------------------------------------	---	---	---------------------------	-------

RADAR REQUIRED

GP 3.00°
TCH 47

6000

5000

3000

2300

3.2 NM

6.3 NM

2.4 NM

4.1 NM

1.2

RW35L

*LNAV only.

*1.2 NM to RW35L

TANDE

CORMN

DALLN

BEGGO

BBAKR

BOSSI

tr 357°

CATEGORY	A	B	C	D
LPV DA	764/18 200 (200-½)			
LNAV/VNAV DA	928/40 364 (400-¾)			
LNAV MDA	1020/24 456 (500-½)		1020/45 456 (500-¾)	

ELEV 607

D

TDZE 564

HIRL all Rwys

REIL Rwy 13L and 31L

TDZ/CL all Rwy except 13L, and 31L

DALLAS-FORT WORTH, TEXAS

Amcl 2B 17AUG17

32°54'N-97°02'W

DALLAS-FORT WORTH INTL (DFW)

RNAV (GPS) RWY 35L