


WAAS CH 63129 W08A	APP CRS 082°	Rwy Idg 3501 TDZE 739 Apt Elev 741
--	------------------------	---

RNAV (GPS) RWY 8

MACKINAC ISLAND (MCD)

RNP APCH.	<div><div>▼</div><div>▲</div></div> Rwy 8 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Pellston altimeter setting and increase all MDA 60 feet, increase LP and LNAV Cat C visibility ½ SM and Circling Cat C visibility ¼ SM. Straight-in and Circling Rwy 8 NA at night.	MISSED APPROACH: Climb to 2500 direct HUVTI and hold.
-----------	---	--

AWOS-3 118.275	MINNEAPOLIS CENTER 134.6 354.05	UNICOM 122.7 (CTAF)	122.8
--------------------------	---	-------------------------------	--------------



4 NM Holding Pattern		Visual Segment - Obstacles.		2500	HUVTI
6000 2500		2400		1240	
7.2 NM		3.6 NM		1.5	
CATEGORY	A	B	C	D	
LP MDA	1080-1 341 (400-1)				NA
LNAV MDA	1120-1	381 (400-1)	1120-1½ 381 (400-1½)	NA	
CIRCLING	1320-1	579 (600-1)	1320-1½ 579 (600-1½)	NA	

ELEV 741	TDZE 739
<div>MIRL Rwy 8-26</div> <div>REIL Rws 8 and 26</div>	