

WAAS CH 58011 W18A	APP CRS 180°	Rwy Idg 3998 TDZE 83 Apt Elev 83
--	------------------------	---

RNAV (GPS) RWY 18

JOHN H HOOKS JR MEML (M79)

RNP APCH - GPS.

NA

Rwy 18 helicopter visibility reduction below 1 SM NA. Straight-in and Circling Rwy 18 NA at night. Use Monroe altimeter setting, when not received, use Bastrop altimeter setting and increase all DA/MDA 20 feet; increase LPV all Cats visibility 1/8 SM. Baro-VNAV NA.

MISSED APPROACH:
Climb to 1600 direct
APERE and hold.

MLU ASOS
125.05

MONROE APP CON ★
126.9

UNICOM
122.8 (CTAF) 0

1149

△

4 NM

HOLD 6000 1700

360°

180°

(IF/IAF)
OGELS

1600

180° (6.9)

(FAF)
YIGLU

ZAPOR 1.3 NM to RW18

△ 298

△ 187±

△ 131±

△ 335

MISSED APCH FIX

APERE

360°

180°

4 NM

30 NM to OGELS (NoPT)

9 NM 2200

1700

090°

270°

OGELS

1700

9 NM 2200

30 NM to OGELS

1600

APERE

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).

4 NM Holding Pattern

360°

180°

6000 1700

GP 3.60° TCH 59

1600

*620

1.3 NM

2.5 NM

6.9 NM

YIGLU 1600

ZAPOR 1.3 NM to RW18

RW18

CATEGORY	A	B	C	D
LPV DA	448-1	365 (400-1)	NA	NA
RNAV/VNAV DA	559-1 3/8	476 (500-1 3/8)	NA	NA
RNAV MDA	480-1	397 (400-1)	NA	NA
CIRCLING	600-1	517 (600-1)	NA	NA

ELEV 83

TDZE 83

180°

81

360°

3998 X 57

36

REIL Rwy 18 and 36 0

MIRL Rwy 18-36 0

RAYVILLE, LOUISIANA
Amdt 1C 29DEC22

32°29'N-91°46'W

JOHN H HOOKS JR MEML (M79)

RNAV (GPS) RWY 18

SC-4, 07 AUG 2025 to 04 SEP 2025

SC-4, 07 AUG 2025 to 04 SEP 2025