

WAAS

CH **40033**

W08A

APP CRS

084°

Rwy Idg

5004

TDZE

170

Apt Elev

176

RNAV (GPS) RWY 8

CAMILLA-MITCHELL COUNTY (CXU)

Baro-VNAV NA when using Albany altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Albany altimeter setting and increase LPV DA to 513 feet; increase LNAV/VNAV DA to 623 feet; increase all MDAs 60 feet and LNAV Cats C/D and Circling Cat D visibility ¼ SM.

MISSED APPROACH:

Climb to 2400 direct CEVOR and hold.

AWOS-3T 118.675	JACKSONVILLE CENTER 125.75 363.075	UNICOM 122.8 (CTAF) 0
---------------------------	--	---------------------------------

The chart displays the RNAV (GPS) RWY 8 approach. Key features include:

- MSA RW08 25 NM** circle with a 2600 ft MSL.
- CEVOR** (CEVOR VORTAC) at 4 NM, 264° bearing, 264° elevation.
- ELMOE** (ELMOE VORTAC) at 2200 ft, 230° bearing, 19.2 NM.
- CEGUK** (IF/IAF) at 1700 ft, 084° bearing, 6.1 NM.
- FETUK** (FAF) at 1700 ft, 084° bearing, 6.1 NM.
- OSUVE** (OSUVE FAF) at 279± ft, 084° bearing, 1.5 NM to RW08.
- RW08** (Runway 08) at 5004 x 100 ft.
- DOGGI** (DOGGI VORTAC) at 2200 ft, 296° bearing, 5.1 NM.
- ZUMOB** (IAF) at 2200 ft, 354° bearing, 5.1 NM.
- Altitudes**: 264°, 370, 580, 554, 619, 601, 1542.

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 39).

2400 CEVOR

GP 3.00° TCH 52

CEGUK

FETUK

OSUVE 1.5 NM to RW08

RW08

*LNAV only.

*680

221±

5004 X 100

26

CATEGORY	A	B	C	D
LPV DA		465-1	295 (300-1)	
LNAV/VNAV DA		575-1⅜	405 (400-1⅜)	
LNAV MDA		540-1	370 (400-1)	
CIRCLING	720-1 544 (600-1)	760-1 584 (600-1)	920-2¼ 744 (800-2¼)	940-2½ 764 (800-2½)

REIL Rwy 8 and 26

MIRL Rwy 8-26

CAMILLA, GEORGIA

Amdt 1C 21APR22

31°13'N-84°14'W

CAMILLA-MITCHELL COUNTY (CXU)

RNAV (GPS) RWY 8