

WAAS CH 40426 W29A	APP CRS 291°	Rwy ldg TDZE 7078 Apt Elev 7096	8900
--	------------------------	---	-------------

RNAV (GPS) RWY 29


RALPH WENZ FLD (PNA)

Baro-VNAV NA. When local altimeter setting not received, use Big Piney altimeter setting and increase LPV DA to 7386 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 7664 feet and all visibilities ½ SM; increase all MDA 60 feet and LNAV Cats C/D visibility ¼ SM. Circling NA south of Rwy 11/29. DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. VDP NA with Big Piney altimeter setting.


ODALS

MISSED APPROACH: Climb to 7600 then climbing left turn to 10000 direct BPI VOR/DME and hold.

AWOS-3 118.325	SALT LAKE CENTER 128.35 239.25	UNICOM 122.8 (CTAF)
--------------------------	--	-------------------------------



ELEV 7096	TDZE 7078
-----------	-----------



7600	10000	BPI	VGSI and RNAV glidepath not coincident (VGSI Angle 2.83/TCH 40).	COTDA
*LNAV only.	*1.5 NM to RW29	PINIY	FEDPA	9400
		8700	8900	291°
		8700	8900	291°
		1.5 NM	3.5 NM	2.1 NM
		5 NM		
CATEGORY	A	B	C	D
LPV DA	7328-¾	250 (300-¾)		
LNAV/VNAV DA	7606-1¾	528 (600-1¾)		
LNAV MDA	7600-1	522 (600-1)	7600-1½	522 (600-1½)
CIRCLING	7640-1	544 (600-1)	7840-2¼	7980-3
			744 (800-2¼)	884 (900-3)