

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Inop table does not apply.

ALSF-2

MISSED APPROACH: Climb to 800, then climbing left turn to 2500 direct EARTH and hold.

ORLANDO APP CON 134.95 281.425	NASA TOWER ★ 128.55 (CTAF) 284.0	GND CON 121.75
-----------------------------------	-------------------------------------	-------------------

ROCIT

2500

GP 3.00°
TCH 55

STARS

1500

RW15

1500

800

2500

EARTH

155°

1500

6.1 NM

3.6 NM

0.9 NM

*0.9 NM to RW15

*LNAV only

CATEGORY	A	B	C	D	E
LPV DA		208-1	200 (200-1)		
LNAV/VNAV DA		286-1	278 (300-1)		
LNAV MDA		360-1	352 (400-1)		
CIRCLING	420-1 411 (500-1)	460-1 451 (500-1)	940-2¾ 931 (1000-2¾)	940-3	931 (1000-3)

TITUSVILLE, FLORIDA

Amndt 1A 25MAY17

SPACE FLORIDA LAUNCH AND LANDING FACILITY (TTS)

28°37'N-80°42'W

RNAV (GPS) RWY 15