

WAAS CH <b>42741</b> <b>W11A</b>	APP CRS <b>111°</b>	Rwy Idg <b>4982</b> TDZE <b>128</b> Apt Elev <b>128</b>
----------------------------------------	------------------------	---------------------------------------------------------------

RNAV (GPS) RWY 11

ST GEORGE (PBV) (PAPB)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -14°C (7°F) or above 47°C (117°F). DME/DME RNP-0.3 NA. Circling NA north of Rwy 11-29. Inop table does not apply to LPV all Cats and LNAV Cat A. For inop ALS, increase LNAV/VNAV all Cats visibility to 2½ SM. For inop ALS, increase LNAV Cat C visibility to 2½ SM.

MAISF

MISSED APPROACH: Climb to 600 then climbing right turn to 3000 direct OSUCA and hold.

ASOS <b>135.45</b>	ANCHORAGE CENTER <b>119.1 339.8</b>	CTAF <b>122.8</b>
-----------------------	----------------------------------------	----------------------

4 NM Holding Pattern

EQQUP

3000

291°

111°

GP 3.60°  
TCH 56

APOTE

2100

WVOG 2.3 NM to RW11

RW11

\*1060

6 NM

2.7 NM

2.3 NM

600

3000

OSUCA

\* LNAV only.

CATEGORY	A	B	C	D
LPV DA	428-1	300 (300-1)		NA
LNAV/VNAV DA	957-2	829 (900-2)		NA
LNAV MDA	900-1	772 (800-1)	900-2 772 (800-2)	NA
CIRCLING	900-1 772 (800-1)	980-1¼ 852 (900-1¼)	980-2½ 852 (900-2½)	NA

ELEV 128

TDZE 128

111° to RW11

4982 X 150

29

REIL Rwy 29

HIRL Rwy 11-29

ST GEORGE, ALASKA

Orig 13SEP18

56°35'N-169°40'W

ST GEORGE (PBV) (PAPB)

RNAV (GPS) RWY 11