RNAV (GPS) RWY 36

VICKSBURG TALLULAH RGNL (TVR)

WAAS	APP CRS	Rwy ldg	5002
Chan 99700	357°	TDZE	86
W36A		Apt Elev	86

T A For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C (18°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Vicksburg Muni, MS altimeter setting and increase LPV DA to 309 feet, LNAV/VNAV DA to 516 feet all visibilities ⅛ mile; increase all MDA 40 feet and visibility Cats C/D¼ mile. Baro-VNAV and VDP NA with Vicksburg Muni, MS altimeter setting.

SSALR A3

MISSED APPROACH: Climb to 2000 direct DEXIW and hold.

ASOS	MEMPHIS CENTER	UNICOM
118.525	132.5 259.1	123.0 (CTAF) L

MISSED APCH FIX









CATEGORY	A	B	C	D
LPV DA		286-½	200 (200-½)	
LNAV/VNAV DA		493-⅞	407 (500-⅞)	
LNAV MDA	480-½	394 (400-½)	480-⅝	394 (400-⅝)
C CIRCLING	540-1	454 (500-1)	720-1¾ 634 (700-1¾)	720-2 634 (700-2)

ELEV 86 D TDZE 86



SC-4, 07 AUG 2025 to 04 SEP 2025
SC-4, 07 AUG 2025 to 04 SEP 2025