RNAV (GPS) RWY 34

AITKIN MUNI/STEVE KURTZ FLD (AIT)

WAAS	APP CRS	Rwy Ldg	4000
CH 82431	344°	TDZE	1206
W34A		Apt Elev	1206

RNP APCH - GPS.

T A Circling NA to Rwys 8 and 26. Rwy 34 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using HZX altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use HZX altimeter setting: increase LPV DA to 1588 feet and all visibilities ⅛ SM; increase LNAV/VNAV DA to 1660 feet and all visibilities ¼ SM; increase all MDAs 40 feet and LNAV visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 3400 direct ZAPUB and hold.

AWOS-3	MINNEAPOLIS CENTER	UNICOM
118.675	118.05 239.0	123.05 (CTAF) L



ELEV 1206 D TDZE 1206



REIL Rwys 16 and 34 L
MIRL Rwy 16-34 L



CATEGORY	A	B	C	D
LPV DA	1548-1⅛ 342 (400-1⅛)			NA
LNAV/VNAV DA	1620-1⅜ 414 (500-1⅜)			NA
LNAV MDA	1720-1 514 (600-1)		1720-1⅜ 514 (600-1⅜)	NA
CIRCLING	1780-1 574 (600-1)		1900-2 694 (700-2)	NA

NC-1, 09 JUL 2026 to 06 AUG 2026
NC-1, 09 JUL 2026 to 06 AUG 2026