WAAS	APP CRS	Rwy Ldg	7976
CH 90411	046°	TDZE	258
W04A		Apt Elev	266

RNAV (GPS) RWY 4L

BILL AND HILLARY CLINTON NTL/ADAMS FLD (LIT)

RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. Rwy 4L helicopter visibility reduction below ¾ SM NA. For inop ALS, increase LNAV Cat A and B visibility to RVR 5000. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations.

MALSR

MISSED APPROACH: Climb to 2900 direct ODXIH and on track 052° to BRAUM and hold.

D-ATIS	LITTLE ROCK APP CON	ADAMS TOWER	GND CON
125.65	135.4 353.6	118.7 257.8	121.9 339.8



ELEV 266 D TDZE 258



CATEGORY	A	B	C	D
LPV DA	544/40 286 (300-¾)			
LNAV/VNAV DA	824-1½ 566 (600-1½)			
LNAV MDA	780/40 522 (600-¾)		780/55 522 (600-1)	
CIRCLING	820-1 554 (600-1)	1000-1 734 (800-1)	1180-2¾ 914 (1000-2¾)	1180-3 914 (1000-3)



MIRL Rwy 18-36
HIRL Rwys 4R-22L and 4L-22R
TDZL/RCLS Rwy 22R

SC-1, 06 AUG 2026 to 03 SEP 2026
SC-1, 06 AUG 2026 to 03 SEP 2026