MINNEAPOLIS DEP CON
SOUTH/EAST 124.7 335.65
NORTH/WEST 125.75 335.65
D-ATIS DEP
120.8
CLNC DEL
133.2
MINNEAPOLIS TOWER
123.95 273.55 (12L-30R)
126.7 273.55 (12R-30L, 4-22)
123.675 273.55 (17-35)
TOP ALTITUDE:
ASSIGNED BY ATC
RADAR required.
FARGO
116.2 FAR
Chan 109
R-116
14000
*3300
296°
(120)
KBREW
14000
HOMUR
55
(21)
34
(113)
HRBEK
293°
(21)
GOPHER
117.3 GEP
Chan 120
R-014
R-031
R-040
REDWOOD FALLS
113.3 RWF
Chan 80
N
MSP
7
MINNEAPOLIS
115.3 MSP
Chan 100
Rwys 30L/R
(For assigned 220° CW 360°)
3500
Rwy 17
(For assigned 230° CW 285°)
3500
FLYING CLOUD
117.7 FCM
Chan 124
Rwys 12L/R
(For assigned 060° CW 100°)
3500
MSP 25 NM
3500
2800
090°
270°
TAKEOFF MINIMUMS
Rwys 12R, 17, 22: Standard.
Rwy 4: Standard with minimum climb of 202'/NM to 3000.
Rwy 12L: 300-1¼ or standard with minimum climb of 276'/NM to 1100,
Rwy 30L: Standard with minimum climb of 208'/NM to 2100.
Rwy 30R: Standard with minimum climb of 217'/NM to 2100.
Rwy 35: Standard with minimum climb of 219'/NM to 2100.
NOTE: Chart not to scale.
(CONTINUED ON FOLLOWING PAGE)